

PVC PERSØ10x16 WD15 ROOD- TRANSP 50M

Product Images



Omschrijving

- **all-purpose luchtslang**
- dicflex - PVC slang

| | rol lengte | kleur | diameter | werkdruk 20°C | temp max °C | barst druk 20°C -bar |
|------------|------------|-------|----------|---------------|-------------|----------------------|
| dicflex 6 | 50 mtr | blauw | 6 x 12 | 15 | 60 | 50 |
| dicflex 8 | 50 mtr | blauw | 8 x 14 | 15 | 60 | 50 |
| dicflex 8 | 50 mtr | rood | 8 x 14 | 15 | 60 | 50 |
| dicflex 10 | 50 mtr | blauw | 10 x 16 | 15 | 60 | 50 |
| dicflex 10 | 50 mtr | rood | 10 x 16 | 15 | 60 | 50 |
| dicflex 13 | 50 mtr | blauw | 13 x 20 | 15 | 60 | 50 |
| dicflex 13 | 50 mtr | rood | 13 x 20 | 15 | 60 | 50 |

Additional Information

| | |
|---------------------------|---------------------------|
| EAN Code | 8719426385838 |
| Artikelnummer | SL.DICFLEX1050KR |
| Omschrijving | Dicflex rood 50 meter |
| Barstdruk bij 23°C (bar) | 50 |
| Merk | Prevost |
| Binnendiameter slang (mm) | 10 mm |
| Buitendiameter slang (mm) | 16 mm |
| Slang type | Lucht, water, olie en vet |
| Werkdruk bij 23°C (bar) | 15 |
| Diameter | 10x16 mm |
| Kleur | Rood |
| Lengte | 50 meter |
| Materiaal | PVC |